

DATALOGGER A 2 CANALI serie : AM88394

2 inputs datalogger series : AM88394



DATALOGGER

2 canali
2 channels

Il datalogger di temperatura AM 88394 è un registratore economico ed affidabile che immagazzina nella sua memoria oltre 16000 misure (8000 per canale) che possono essere scaricate su PC tramite il software in dotazione. I tempi di campionamento sono programmabili da 1 secondo fino a 24 ore. Il display LCD visualizza la temperatura rilevata in ambiente. Dispone di un pulsante START/STOP per avviare ed arrestare la registrazione. Può essere anche usato come indicatore di temperatura ambiente con la funzione STAND BY.

AM88394 datalogger is an economic and reliable recorder that store 16000 sampling points (8000 per channels) that will be download by USB cable and software. The sampling points are programmable from 1 seconds up to 24 hours. The LCD display shows the ambient temperature. It has START/STOP button for launch and stop the recording. It can be used as ambient temperature indicator with STAND BY function.

CARATTERISTICHE TECNICO - COSTRUTTIVE DESIGN FEATURES

CONDIZIONI D'ESERCIZIO :

Umidità : 0-80% RH
Temperatura : da 0°C a +50°C

OPERATING CONDITIONS :

Humidity : 0-80% RH
Temperature : from 0°C to +50°C

CARATTERISTICHE COSTRUTTIVE :

Dimensioni : 75,5*53*23,5 mm
Dimensioni display : 33*13 mm
Scala : da -30°C a +85°C; sonda esterna da -40°C a +100°C
Precisione : $\pm 0,6^\circ\text{C}$ da -20°C a +50°C ($\pm 1,2^\circ\text{C}$ oltre)
Risoluzione : 0,1°C
Capacità memoria : 16000 registrazioni (8000 per canale)
Alimentazione : 1 batteria tipo CR2 (durata media 6 mesi)
Accessori inclusi nella fornitura : cavo USB / software / batteria / manuale d'istruzioni

DESIGN FEATURES :

Dimensions : 75,5*53*23,5 mm
Display dimensions : 33*13 mm
Range : from -30°C to +85°C; external probe from -40°C up to +100°C
Accuracy : $\pm 0,6^\circ\text{C}$ from -20°C to +50°C ($\pm 1,2^\circ\text{C}$ others)
Resolution : 0,1°C
Data capacity : 16000 records (8000 for each channel)
Power supply : CR2 battery (life time 6 months)
Included accessories : USB cable / software / battery / instructions manual

